



Fan Controls Fan Controls

Accessories that help achieve energy savings by controlling on demand

We offer controls designed for all inline duct fans:

- · Speed controls
- Electronic timers
- Thermostats
- Switches
- Dehumidistats

Explore the range in the dropdown menu.

Find more details in our online catalogue

EC-10V Speed Control

The EC-10V potentiometer infinitely controls the fan speed of inline duct fans such as FG.. EC, FKD.. EC, prioAIR.. EC via a stepless control signal by adjusting the rotary knob.

Supply voltage: 10V DC.

Output voltage: 0V (OFF) to 10V (FULL SPEED).

The EC-10V is shipped without a décor plate. The décor plate is

standard.

WC / RPE Speed Control

WC and RPE are heavy-duty rotary-type variable speed controllers with

an ON/OFF switch.

Supply voltage: 120V/1~ (230V/1~)

Output voltage: varies

Amperage: 5A, 10A, 15A (120V) and 10A (230V) Brushed aluminum switch plate and screws are included.

IPF05 Fan Speed Control

The IPF05 speed control features a low-profile fluid slide bar movement for fine adjustment of fan speeds.

Easy-to-use ON/OFF preset switch controls the fan without disturbing your favorite pre-selected settings.

Built-in LED locator light illuminates when the load is off.

Designed for both single-pole (one-location) and 3-way (multi-location) applications. RFI noise suppression.

Ivory and Light Almond color change kits are included.

IPF05 was sold as 6637-PW in the past.

PT6

The PT6 is designed to efficiently decrease attic heat and moisture, triggered by temperature changes.

- Adjustable temperature range: 60°-120° F (16°-49° C)
- · Galvanized steel housing
- · Wired for fast and easy installation
- 15 amps
- · UL listed

This not only ensures a stable temperature in the attic space but also enhances the overall performance of the forced air system.

Recommended setting of 95°F (35°C).