# EDF7

# Electronic Multifunction Dehumidistat

Product #: 44883



An electronic multifunction dehumidistat that is compatible with all Fantech's HRV/ERV (except SH/VH 704). This control has 3 possible modes of operations: Ventilation mode, Recirculation mode and Standby.

# **Auto Setting**

In AUTO Setting, the EDF7 will activate normal speed ventilation when the indoor relative humidity is above the desired set point. During summer, the AUTO Setting can be deactivated to lower energy consumption.

#### **Features**

- Preferences for desired indoor relative humidity range
- 1" x 1" (3cm x 3cm) LCD backlit touch screen
- Ventilation mode is displayed on screen
- Indoor relative humidity displayed when AUTO Setting is activated
- No battery to replace

#### **External dimensions**

The wall control has a dimension of 3  $^{5}/_{8}$ " wide x 4  $^{7}/_{8}$ " high x  $^{7}/_{8}$ " thick (91 mm x 124 mm x 22 mm).

# **Display**

Backlit blue in color

# Sensor accuracy

 $\pm$  5% (depends on the room's air movement).

#### Communication

Proprietary 2 wire interface, 12Vdc not polarity sensitive

#### Supply volatage

12Vdc not polarity sensitive

#### Connector

2 wire screw terminal up to 18 AWG

#### **Plastics**

WHITE CWL 9519, Smooth matte surface finish

#### **Backplate**

Can be mounted using screws on drywall and/or on electrical enclosure NEMA 5-15R (Residential 120Vac single enclosure)

# **Ventilation Mode**


There are 3 possible ventilation modes. VENTILATION, RECIRCULATON, STANDBY/OFF

# Warranty


2 year warranty



# **Dimensions**



#### Icons



#### **Contacts**

Submitted by:		Date:	
Quantity:	Model:	Project #:	
Comments:			
Location:			
Architect:			
Engineer:		Contractor:	

# Distributed by:



United States 10048 Industrial Blvd. • Lenexa, KS 66215 • 1.800.747.1762 • www.fantech.net Canada 50 Kanalflakt Way • Bouctouche, NB E4S 3M5 • 1.800.565.3548 • www.fantech.net

