RTS-W

Wireless 20/40/60 min push-button timer
Product #: 414920

A wireless 20/40/60 minute push-button timer that connects to the ECO-Touch® Auto IAQ controllers. The RTS-W allows you to easily add exhaust controllability to areas that need it most. It activates the system on maximum ventilation for either 20, 40, or 60 minutes depending on your selection. Afterwards, it returns to the predetermined setting.

Features
- Wireless connectivity
- Single push button control to simplify ventilation needs
- LED lights that correspond with the pressed button
- Limited 2 year warranty

Specifications
- External Dimensions: 4 $\frac{1}{8}$ in. (Length) x 1 $\frac{5}{16}$ in. (Width) x $\frac{17}{32}$ in. (Depth) (104mm x 33mm x 14mm)
- Communication: Wireless pairing with ECO-Touch® Auto IAQ controller
- Power: CR2450 3V battery

Timer Modes
There are 3 possible timer modes: 20, 40, and 60 minutes. These 3 modes will activate the ventilation system and have it operate on maximum speed for the selected time. Afterwards, it returns to the predetermined setting.

Operation Mode
When a mode is selected, the corresponding indicator light will illuminate on the control. Press the button once to operate the system for 20 minutes, press it twice to operate the system for 40 minutes, and press it three times to operate the system for 60 minutes. Press the button four times to set the ventilation system to standby.

Plastics
WHITE CWL 9519, Smooth matte surface finish

### Backplate
Can be mounted using screws on drywall and/or on electrical enclosure NEMA 5-15R (Residential 120Vac single enclosure)

fantech®
a systemair company

Dimensions

Model	A		B		C		D		E		F		G		H		I		J	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm
RTS-W	4 1/8	104	7/8	22	17/32	14	3/32	2	2 7/16	61	1 1/8	28	3/32	2	1 5/16	33	5 5/8	66	9/16	15

Icons

LED Lights

Button

LED Lights

Contacts

Submitted by: _____ Date: _____
Quantity: _____ Model: _____ Project #: _____
Comments: _____
Location: _____
Architect: _____
Engineer: _____ Contractor: _____

Distributed by:

fantech ®
a systemair company