

## bathfan Simple SMPL80 Series

Bathroom Exhaust Fans



SMPL 80 L

Simple CFM Lit

SMPL80 Part # – 484300  
SMPL80L Part # – 484301

With 80 CFM of airflow capability, these bathroom exhaust fans offer high quality performance with wall or ceiling mount options. The product is powered by an Alternating Current (AC) motor to enable high energy-efficiency and long lasting reliability. Includes one (1) hanger bar to enable a multitude of installations. Available in lighted or non-lighted models.

### Features

- 80 CFM (38 L/s) @ 0.1 in. wg
- Quiet operation
- Low Profile Design – ideal for 2x4 joist construction and taller
- Energy-efficient, permanently lubricated motor
- Lighted grille (on SMPL80L models only)
- Mount in the wall or in the ceiling
- Built-in, soft-close backdraft damper
- Includes one adjustable hanger bar to fit a multitude of applications
- Duct connector included

### Specifications

• Airflow	80 CFM (38 L/s) @ 0.1 in. wg. (25 Pa)
• Sones	1.1
• Duct size	4 in. (101mm)
• Voltage/Phase/Hz	120/1/60
• Power rated	18.1W
• Amp	0.25A

### Requirements and Standards

- ETL listed
- ENERGY STAR® certified
- Complies with California Title 24
- HVI 2100 certified

### Casing

Constructed of 26 gauge galvanized steel for corrosion resistance. Detachable 4 in. (101mm) duct connector that includes a lightweight, built-in, soft-close backdraft damper. The included hanger bar mounting bracket is adjustable up to 14–24 in. (356mm–610mm) to allow for ideal positioning.

### Motor/Blower

Plug-in, permanently-lubricated, ENERGY STAR® certified motor with thermal overload protection to ensure longer motor life. ETL and cETL listed for tub/shower enclosure when used with a GFCI branch circuit.

### Grille

Low profile: constructed of a rugged polymeric resin known for its long life durability. Powerful torsion springs seat the trim tightly and evenly to the ceiling surface. Includes an 11W, 4000K cool white LED lighted grille (on SMPL80L models only).

### Installation

For ceiling or wall mounting installations. Can be installed directly onto joists or with the help of the single hanger bar.

### Ceiling Radiation Damper

bathfan Simple (SMPL) Series to be used with the UL555C Fantech Ceiling Radiation Damper—Small (Model #: 98599, sold separately) or the UL555C Fantech Ceil. Radiation Damper (Model #: 484374, sold separately).



### Limited Warranty

5 years



## Dimensions

Model	A		B		C		D		E		F	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm
SMPL80	10-1/4	260	4	102	10-1/4	260	3-3/8	86	13-3/4	321	13	330
SMPL80L												

**SMPL80, #484300**



**SMPL80L, #484301**



## HVI Performance

### SMPL80 #484300

4 in. (101mm) Duct

0.1 (25) in. wg. (Pa)


Air volume in CFM (L/s)	Noise (Sones)	Rated power (W)
80 (38)	1.1	18.1

### SMPL80L #484301

4 in. (101mm) Duct

0.1 (25) in. wg. (Pa)

Air volume in CFM (L/s)	Noise (Sones)	Rated power (W)
80 (38)	1.1	18.1



## Contacts

Submitted by:	Date:
Quantity:	Model:
Comments:	Project #:
Location:	
Architect:	
Engineer:	Contractor:

## Distributed by:

