


5DDD Series

Direct Drive Downblast Roof Ventilator



STANDARD FEATURES

- All ventilators are UL 705 Standard listed
- One-piece removable exhaust hood
- Inlet temperatures up to 170°F
- Backward inclined aluminum fan wheel
- Equipped with a built-in bird screen to protect discharge
- Externally cooled motor compartment



Fantech Inc. certifies that the 5DDD Series shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.

Model	A	B	C	D	Model	A	B	C	D
5DDD 085A	19	18 ⁷ / ₈	13 ¹ / ₄	3 ¹ / ₂	5DDD 13DB	22	25 ⁵ / ₈	18 ¹ / ₈	4 ³ / ₈
5DDD 106A	19	22 ³ / ₈	16 ¹ / ₂	3 ³ / ₈	5DDD 15CA	26	27 ⁷ / ₈	18 ¹ / ₂	4 ³ / ₈
5DDD 10AA	19	22 ³ / ₈	16 ¹ / ₂	3 ³ / ₈	5DDD 16DB	26	29 ³ / ₄	20 ¹ / ₄	4 ³ / ₄
5DDD 12CA	22	24 ¹ / ₄	17 ¹ / ₈	4	5DDD 18EB	30	31 ⁵ / ₈	21 ³ / ₈	5 ⁵ / ₈

All dimensions in inches.

Fan Specifications							Motor Specifications				
Line	Qty	Model No.	Tag	CFM	SP	Fan RPM	Watts	Volts	Phase	Hertz	Encl
1											
2											
3											
4											

Accessory Items	1	2	3	4	Accessory Items	1	2	3	4

Project: _____ Submitted: _____
 Customer: _____ Approved: _____
 Location: _____

United States 10048 Industrial Blvd. • Lenexa, KS 66215 • 1.800.747.1762 • www.fantech.net
Canada 50 Kanaflikt Way • Bouctouche, NB E4S 3M5 • 1.800.565.3548 • www.fantech.net

Fantech reserves the right to make technical changes.
 For updated documentation please refer to www.fantech.net

